



Free flow non-shrink high strength grouts

Description:

A single pack ready to use high strength, free flowing non-shrink grout. CETPATCH GP is blend of specially processed cement and special fillers free from corrosive substances and additives.

Advantages:

- Pre packed : No batching or blending errors consistency in performance form batch to batch.
- Non - shrink : Eliminates shrinkage commonly encountered in both plastic and hardened phases.
- Free flow : Free flowing self-levelling grout. Easy placement and filling of under based of machinery.
- High strength: Early load transfer and rapid installation.
- Iron free : No deterioration of grout due to rust expansion.

Area of application:

Ideal for use for base plated and bolt pockets of stanchions and all machinery and equipment

Properties:

- Yield per 30 Kg. : 15 Litters approx...
- Water cement ration : Pourable – 4.8 Lt. (W / P : 0.16)
Flowable - 5.4 Lt. (W / P : 0.18)
- Pourable Life : 20 minutes.
- Expansion (% Vol..) : 0.8
- Compressive strength : Kg / cm²

Consistency	1 days	3 days	7 days	28days
Pourable (W/P : 0.16)	250	340	480	690
Flowable (W/P : 0.18)	240	320	450	630

Packing: Supplied in 30 kg

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products

Ashapura Minechem Ltd.

Head Office: Jeevan Udyog Building

3rd Floor, 278, D. N. Road, Fort

Mumbai -400 001 (India)

Email: info@ashapura.com | www.ashapura.com

Phone: Mumbai +91 22 6665 1700 | Ahmedabad 079 – 40063751 / 4

CIN No.: L14108MH1982PLC026396



Ashapura
Group Of Industries
Since 1960