



CETCRETE PDP+

1217

Acrylic Polymer Emulsion for Paints, Distempers & Putty

Advantages:

- Suitable for all type of paint, Distempers & Putty
- Excellent scrub resistance with special Crosslinking Polymer.
- Excellent resistance to water.
- Superior finish, Economical cost cutting & easy to use.

Area of application:

- Paint, Distempers & Putty

Direction of use:

- Cetcrete PDP+ should be added with the measured gauge water.
- It should not be added to the directly in paints, Distempers or Dry powder of Wall Putty.
- 1 kg cetcrete PDP+ for 20 kg paints or Distempers and 40 kg wall putty cetcoat SF or Lotus should be adjusted by 35-40% of water to stiff consistency by using suitable mixer.
- Leave the mixture for 5 minutes, remix again & use.

Packing: Supplied in 1 kg, 4 kg, & 20 kg

Disclaimer: The product information & application details given by the company & its agents have been provided only as a general guideline for usage. No guarantee / warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products

Ashapura Minechem Ltd.

Head Office: Jeevan Udyog Building

3rd Floor, 278, D. N. Road, Fort

Mumbai -400 001 (India)

Email: info@ashapura.com | www.ashapura.com

Phone: Mumbai +91 22 6665 1700 | Ahmedabad 079 – 40063751 / 4

CIN No.: L14108MH1982PLC026396



Ashapura
Group Of Industries
Since 1960